

HT11 Series Tower Online UPS 6-20kVA (220V/230V/240V)

Ht11 series, ranging from 6kVA to 20kVA, is double conversion online UPS with fully DSP controlled technology. The single phase UPS applies the advanced 3-level technology, achieving a efficiency up to 95%. With its compact design of high power density (kW=kVA), HT11 series make it ideal choice for computers, telecommunication equipment and other sensitive devices.



Application

IDC(Internet Data Center),network,servers and workstations,office etc

Features

- High efficiency, up to 95%
- kVA=kW, Output PF=1
- 3 level of technology, compatible with complicated load
- Battery number can be set on LCD
- Intelligent charging management, effectively improving the life time of battery
- Smaller size with higher power density
- Parallel up to 4 units
- 12A charger for option, charging for large capacity batteries

Specification

MODEL	HT1106XS	HT1106XL	HT1110XS	HT1110XL	HT1115XL	HT1120XL
Capacity	6kVA/6kW	6kVA/6kW	10kVA/10kW	10kVA/10kW	15kVA/15kW	20kVA/20kW
Phase	Single phase in , Single phase out					
Input voltage range	110Vac~288Vac 100% load@ > 176Vac; 90% load@ > 160Vac 80% load@ > 140Vac; 70% load@ > 132Vac; 60% load@ > 110Vac					
Input THDi	≤4%@100% load; ≤6%@50% load (linear load)					
Input PF	≥0.99					
Input frequency range	40Hz-70Hz					
Output PF	1					
Output voltage	220V/230V/240V					
Voltage regulation	±1%					
THDu	≤2%(linear) ; ≤5% (non-linear)				≤1%(linear) ; ≤3% (non-linear)	
Battery voltage	192Vdc					
Battery type/number	12V, 7/9Ah*16	External	12V,9Ah*16	External	External	
System efficiency	Normal mode: 95%					
Noise(1 meter away)	<45dB@<70%load; <50dB@>70%load				<50dB@<70%load; <58dB@>70%load	
Overload capability (Inverter mode)	105-110%: for 10 min; 130%: for 1 min; 150%: for 30 second					
Overload capability (Battery mode)	110%: shut down after 1 min; 130%:shut down after 10 second; >130%: shut down after 200 ms					
Crest factor	3:1					
Display	LED+LCD					
Interface	Standard:RS232 Optional: SNMP, USB, RS485,Dry Contacts,Parallel Kit					
W*D*H (mm)	190*426*705	190*426*336	190*485*705	190*485*336	190*485*480	
Package Weight (kg)	56	14	60	16	33	